









Notes:

- Electrical Specifications:
 - Meets EIA/TIA-568-B.2 Cat.5e Specification
 - Contact Resistance: 20mOhm max.
 - Insulation Resistance: 500MOhm min. @ 100 VDC
 - Current Rating: 1.2A max. at 25°C
 - Working Voltage: 100 VDC
 - DWV: 1000 VDC/60s Contact to Contact, 1500 VDC/60s Contact to Metal Shell
 - Operating Temperature: -40°C to +85°C
- Material and Finish:
 - Receptacle Housing & Protective Cover: ABS, Nickel Plated; UL94 V-0
 - Panel Nut: Brass, Finish: Nickel Plated
 - Panel Gasket: Silicon, Color: White
 - Cover Gasket: Silicon, Color: White
 - Tether: Polycarbonate, Color: Black
 - Cat.5e RJ45 PCB Jack Metal Shell: Copper Alloy, Nickel Plated
 - Cat.5e RJ45 PCB Jack Plastic Housing: Glass filled PBT UL94 V-0, Color: Black
 - Cat.5e RJ45 PCB Jack Contacts: Phosphor Bronze, Finish: 50u" Gold min. over Nickel
- Connector can be front or rear mounted to a maximum panel thickness of 3.2mm.
- IP67 rated when covered or fully mated with the appropriate mating connector
- Recommended Mounting Panel Nut torque is 20 to 25 lb-inch
- Supplied with a cable tie

RoHS compliant

Description	Part Number
Metallized Plastic Version	17-111034
Potted Metallized Plastic Version	17-111044

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC CORPORATION	DOT NOT ALTER CAD DRAWING BY HAND	Customer:			Tolerance Unless otherwise specified			Scale:		Dim. in mm			
		Name		Title	Approval Date	0 PLC ±0.50 1 PLC ±0.30 2 PLC ±0.25 3 PLC ±0.10 ANGLES ±3°		Autodesk Inventor		Material: See Notes			
								2012	Date	Name	Receptacle + Cover Assembly Kit with Cat. 5e RJ45 PCB Jack Version-III Metallized Plastic Version		
								Draw.	Nov. 19	Vincent Ke			
								Appd.	Nov. 19	J. Chaudry			
								Norm					
								D-old			Drawing No.: 17K1A377		DIN A3
		1 x b	Ä21-0426	03.11.2021	Bub								
		a	original										
		Rev.	Changes	Date	Name							Part No.: SEE PART NUMBER TABLE	