







Recommended Double-D Panel Cutout



Recommended Round Panel Cutout



Notes:




1. Electrical Specifications:

- Meets EIA/TIA-568-B.2 Cat.5e Specification
- Contact Resistance: 20 mOhm max.
- Insulation Resistance: 500MOhm min. @ 100 VDC
- Current Rating: 1.2A max. at 25°C
- Working Voltage: 100 VDC
- DWV: 1000 VDC/60s Contact to Contact, 1500 VDC/60s Contact to Metal Shell
- Operating Temperature: -40°C to +85°C

2. Material and Finish:

- Receptacle Housing (with Flange): Zinc Die-Cast, Finish: Nickel Plated
- RJ45 Jack Metal Shell: Copper Alloy, Nickel Plated
- RJ45 Jack Plastic Housing: Glass filled PBT UL94 V-0, Color: Black
- RJ45 Jack Contacts: Phosphor Bronze, Finish: 50u" Gold min. over Nickel
- Terminal Block Insulator: Polyamide, UL94 V-0 Rated
- Terminal: Brass, Tin Plated
- Gage Clamp: Brass, Tin Plated
- M2 Screw: Steel, Zinc Plated
- Panel Gasket: NBR, Color: Black
- M3 Mounting Hardware: Stainless Steel

- Includes 4 x (Screw + Nut + Flat Washer + Spring Lock Washer)
- 3. Connector can be front or rear mounted to a maximum panel thickness of 3.2mm.
- 4. IP67 rated when covered or fully mated with the appropriate mating connector
- 5. Hardware shipped unassembled
- 6. Recommended M3 screw mounting torque: 8 to 10 lb-inch



Directive 2002/95/EC RoHS Compliant

Description	Part Number
Nickel Plated Zinc Die-Cast with Cat5e RJ45 Jack with Terminal Block	17-111134
Potted Nickel Plated Zinc Die-Cast with Cat5e RJ45 Jack with Terminal Block	17-111144

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY MANNER WITHOUT THE WRITTEN PERMISSION OF CONEC CORPORATION. OWNERSHIP AND COPYRIGHT OF CONEC CORPORATION. DO NOT ALTER CAD DRAWING BY HAND	Customer:			Tolerance Unless otherwise specified		Autodesk Inventor	Scale:	Dim. in mm
	Name	Title	Approval Date	0	PLC	± 0.30	Material: See Notes	Cat. 5e RJ45 + Terminal Block Receptacle (with Flange) Assembly Kit Nickel Plated Zinc Die-Cast Version
				1	PLC	± 0.20		
				2	PLC	± 0.10		
				3	PLC	± 0.05		
					ANGLES	± 1°		
	b	1 x b	Mar/07/2013	Vincent Ke	Norm		Drawing No.: 17K1A382	DIN A3
	a	original			D-old		Part No.: SEE PART NUMBER TABLE	Sheet 1/1
	Rev.	Changes	Date	Name				